 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 1 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name/designation : Naphtha (petroleum), full-range straight-run  
 EC Index : 649-265-00-X  
 EC No : 265-042-6  
 CAS No. : 64741-42-0

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Main use category : Industrial use, Professional use

### 1.3. Details of the supplier of the safety data sheet

Company : Mercuria Energy Trading B.V. supplying for and on behalf of Mercuria Energy Trading S.A  
 Herculesplein 108  
 3584AA Utrecht , Netherlands  
 Telephone +41 22 594 7000  
 Telefax: +41 22 594 3904  
 E-mail: emergency@sgs.com

### 1.4. Emergency telephone number

Emergency telephone : +32 3 575 11 30 (SGS 24/7 Emergency Hotline)

#### IRELAND (REPUBLIC OF)

National Poisons Information Centre  
 Beaumont Hospital

+353 18 37 99 64/+353 1 809 21 66

#### UNITED KINGDOM

National Poisons Information Service  
 (Newcastle Centre)  
 Regional Drugs and Therapeutics Centre,  
 Wolfson Unit

0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### 2.1.1. Classification according to Regulation (EU) 1272/2008


CLP-Classification : The product is classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

Flam. Liq. 1 H224  
 Skin Irrit. 2 H315  
 Muta. 1B H340  
 Carc. 1B H350  
 Repr. 2 H361fd  
 STOT SE 3 H336  
 Asp. Tox. 1 H304  
 Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

#### 2.1.2. Classification according to EU Directives 67/548/EEC or 1999/45/EC

Classification : This substance is classified as hazardous according to 67/548/EEC.  
 Carc.Cat.2; R45  
 Muta.Cat.2; R46

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 2 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

Repr.Cat.3; R62  
 Repr.Cat.3; R63  
 F+; R12  
 Xn; R65  
 Xi; R38  
 N; R51/53  
 R67

Full text of R-phrases: see section 16

**2.2. Label elements**

**2.2.1. Labelling according to Regulation (EU) 1272/2008**

Hazard pictograms :



Signal word :

Hazard statements :

- : Danger
- : H224 - Extremely flammable liquid and vapour.
- : H304 - May be fatal if swallowed and enters airways.
- : H315 - Causes skin irritation.
- : H336 - May cause drowsiness or dizziness.
- : H340 - May cause genetic defects.
- : H350 - May cause cancer.
- : H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.
- : H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements :

- : P201 - Obtain special instructions before use.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- : P273 - Avoid release to the environment.
- : P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- : P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/.
- : P331 - Do NOT induce vomiting.

**2.2.2. Labelling according to Directives (67/548 - 1999/45)**

Not relevant

**2.3. Other hazards**


Other hazards :

- : Vapours can form explosive mixtures with air.
- Results of PBT and vPvB assessment :
- This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Substance name	Product identifier	%	Classification according to Directive 67/548/EEC
Naphtha (petroleum), full-range straight-run	(CAS No.) 64741-42-0 (EC No) 265-042-6 (EC Index) 649-265-00-X	100	Carc.Cat.2; R45 Muta.Cat.2; R46 Repr.Cat.3; R62 Repr.Cat.3; R63 F+; R12 Xn; R65 Xi; R38 N; R51/53 R67

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<h1>SAFETY DATA SHEET</h1>	Page : 3 / 14
		Revision nr : 1
	<h2>Naphtha (petroleum), full-range straight-run</h2>	Issue date : 04/02/2015
		Supersedes :

Substance name	Product identifier	%	Classification according to Directive 67/548/EEC
Toluene	(CAS No.) 108-88-3 (EC No) 203-625-9 (EC Index) 601-021-00-3	>= 3	Repr.Cat.3; R63 F; R11 Xn; R65 Xn; R48/20 Xi; R38 R67
n-Hexane	(CAS No.) 110-54-3 (EC No) 203-777-6 (EC Index) 601-037-00-0	>= 3	Repr.Cat.3; R62 F; R11 Xn; R65 Xn; R48/20 Xi; R38 N; R51/53 R67
Benzene	(CAS No.) 71-43-2 (EC No) 200-753-7 (EC Index) 601-020-00-8	>= 0,1	F; R11 Carc.Cat.1; R45 Muta.Cat.2; R46 T; R48/23/24/25 Xn; R65 Xi; R36/38

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), full-range straight-run	(CAS No.) 64741-42-0 (EC No) 265-042-6 (EC Index) 649-265-00-X	100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361fd STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	(CAS No.) 108-88-3 (EC No) 203-625-9 (EC Index) 601-021-00-3	>= 3	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
n-Hexane	(CAS No.) 110-54-3 (EC No) 203-777-6 (EC Index) 601-037-00-0	>= 3	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Benzene	(CAS No.) 71-43-2 (EC No) 200-753-7 (EC Index) 601-020-00-8	>= 0,1	Flam. Liq. 2, H225 Carc. 1A, H350 Muta. 1B, H340 STOT RE 1, H372 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315

Full text of R- and H-phrases: see section 16


### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical advice/attention.
Skin contact	: Wash with plenty of soap and water. When in doubt or if symptoms are observed, get medical advice. Remove contaminated clothing and wash it before reuse.
Eye contact	: Rinse immediately carefully and thoroughly with eye-bath or water. When in doubt or if symptoms are observed, get medical advice.

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 4 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

- In case of ingestion : Rinse mouth thoroughly with water.  
Do NOT induce vomiting.  
Get immediate medical advice/attention.
- Additional advice : First aider: Pay attention to self-protection!  
Personal protection equipment: see section 8  
Treat symptomatically.  
Never give anything by mouth to an unconscious person or a person with cramps.  
When in doubt or if symptoms are observed, get medical advice.  
Show this safety data sheet to the doctor in attendance.

#### **4.2. Most important symptoms and effects, both acute and delayed**

- Inhalation : May cause drowsiness or dizziness. Vapours may cause drowsiness and dizziness. The following symptoms may occur: Cough, Mental confusion  
Headache.
- Skin contact : Causes skin irritation. The following symptoms may occur: erythema (redness).
- Eye contact : Contact with eyes may cause irritation. The following symptoms may occur: erythema (redness).
- Ingestion : May be fatal if swallowed and enters airways. The following symptoms may occur: Central nervous system depression.
- Other adverse effects : Suspected of damaging fertility. Suspected of damaging the unborn child.  
May cause cancer. May cause genetic defects.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**


- Suitable extinguishing media : Water spray, alcohol resistant foam, Dry extinguishing powder, Carbon dioxide
- Extinguishing media which must not be used for safety reasons : Strong water jet

#### **5.2. Special hazards arising from the substance or mixture**

- Fire hazard : Extremely flammable liquid and vapour.
- Specific hazards : Heating causes rise in pressure with risk of bursting.  
Vapours can form explosive mixtures with air.  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.  
Hazardous decomposition products  
Carbon oxides (COx)  
Organic compounds  
as appropriate :  
Hydrogen sulfide (H2S)  
Sulphur oxides  
Sulphuric acid  
Do not allow run-off from fire-fighting to enter drains or water courses.  
Dispose according to legislation.

#### **5.3. Advice for firefighters**

- Advice for firefighters : Special protective equipment for firefighters.  
In case of fire: Wear self-contained breathing apparatus.  
Use water spray jet to protect personnel and to cool endangered containers.  
Evacuate area.

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 5 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

Do not allow run-off from fire-fighting to enter drains or water courses.  
Dispose according to legislation.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel :
- Evacuate area.
  - Stay upwind/keep distance from source.
  - Provide adequate ventilation.
  - Use personal protective equipment as required.
  - Personal protection equipment: see section 8
  - Avoid contact with skin, eyes and clothes.
  - Do not breathe vapour/spray.
  - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - Ensure that the equipment is adequately grounded.
  - Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
  - Use only non-sparking tools.
  - As appropriate :
    - Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.
- For emergency responders :
- Ensure procedures and training for emergency decontamination and disposal are in place.
  - Personal protection equipment: see section 8 .

### 6.2. Environmental precautions

- Environmental precautions :
- Do not allow to enter into ground-water, surface water or drains.
  - If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up :
- Use foam on spills to minimise vapours.
  - Stop leak if safe to do so.
  - Clean-up methods - small spillage: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents)., Collect in closed and suitable containers for disposal.
  - Clean-up methods - large spillage: Use foam on spills to minimise vapours., Dam up., Large spills should be collected mechanically (remove by pumping) for disposal., Collect in closed and suitable containers for disposal.
  - Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.
  - Dispose of waste product or used containers according to local regulations.


### 6.4. Reference to other sections

Personal protection equipment: see section 8,  
Disposal: see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Handling :
- Obtain special instructions before use.
  - Do not handle until all safety precautions have been read and understood.
  - Provide adequate ventilation.
  - Use personal protective equipment as required.
  - Personal protection equipment: see section 8

	<b>SAFETY DATA SHEET</b>	Page : 6 / 14
		Revision nr : 1
		Issue date : 04/02/2015
	<b>Naphtha (petroleum), full-range straight-run</b>	Supersedes :

Avoid contact with skin, eyes and clothes.  
 Do not breathe vapour/spray.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Ensure that the equipment is adequately grounded.  
 Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.  
 Use only non-sparking tools.  
 Take any precaution to avoid mixing with incompatible materials.  
 See also section 10.  
 Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time).  
 Do not allow contact with soil, surface or ground water.  
 as appropriate  
 Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Advices on general occupational hygiene :

Keep good industrial hygiene.  
 Wash hands before breaks and immediately after using the product.  
 Take off contaminated clothing.  
 When using do not eat, drink or smoke.  
 Keep work clothes separately.  
 Keep away from food, drink and animal feedingstuffs.  
 Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage :

Storage of flammable liquids  
 Keep in a dry, cool and well-ventilated place.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Open valve slowly to avoid pressure shock.  
 Do not store near or with any of the incompatible materials listed in section 10.  
 Protect from sunlight.  
 Bund storage facilities to prevent soil and water pollution in the event of spillage.  
 As appropriate :  
 Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Packaging materials :

Keep/Store only in original container.  
 Suitable material: Mild steel, Stainless steel  
 Unsuitable material: synthetic material

**7.3 Specific end use(s)**


see attached exposure scenario.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

Exposure limit values :

Not applicable

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 7 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :


## 8.2. Exposure controls

Personal protection equipment	:	The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	:	In case of insufficient ventilation, wear suitable respiratory equipment. Filter type: ABEK (EN 141) Half-face mask (DIN EN 140) Full face mask (EN 136) Self-contained open-circuit compressed air breathing apparatus (EN 137) The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection	:	Wear chemically resistant gloves (tested to EN374) ,NBR (Nitrile rubber) > 0,3 mm, BTT: >480 min, The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	:	Use suitable eye protection. (EN 166) Goggles
Body protection	:	Wear suitable coveralls to prevent exposure to the skin. Chemical protection clothing Antistatic clothing In case of large spillages: Wear full chemical protective clothing.
Thermal hazard protection	:	Not required under normal use. Use dedicated equipment.
Engineering control measures	:	Provide adequate ventilation. Safe handling: see section 7 Use only outdoors or in a well-ventilated area. Store locked up. Transfer and handle product only in closed systems. Take precautionary measures against static discharges. Ensure that the equipment is adequately grounded. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
Environmental exposure controls	:	Do not allow to enter into surface water or drains. Comply with applicable Community environmental protection legislation. Do not allow contact with soil, surface or ground water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	colourless
Odour	:	petroleum hydrocarbon odour
Odour threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	< 0 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable, liquid
Upper/lower flammability or explosive limits	:	No data available

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 8 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

Vapour pressure	: < 758 hPa (at 37.7 °C)
Vapour density	: No data available
Density	: 0,688 - 0,701 g/cm <sup>3</sup> (at 15 °C)
Relative density	: No data available
Water solubility	: No data available
Solubility in different media	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Explosive properties	: Not applicable The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.

#### **9.2. Other information**

No data available

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

Reactivity : Extremely flammable liquid and vapour.  
Reference to other sections: 10.4 & 10.5

#### **10.2. Chemical stability**

Stability : The product is stable under storage at normal ambient temperatures.

#### **10.3. Possibility of hazardous reactions**

Possibility of hazardous reactions : Vapours can form explosive mixtures with air.

#### **10.4. Conditions to avoid**

Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Safe handling: see section 7

#### **10.5. Incompatible materials**

Incompatible materials : Oxidising substances, Safe handling: see section 7

#### **10.6. Hazardous decomposition products**

Hazardous decomposition products : Burning produces noxious and toxic fumes. Reference to other sections: 5.2


### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

<b>Naphtha (petroleum), full-range straight-run (64741-42-0)</b>	
LD50/oral/rat	> 7000 mg/kg
LD50/dermal/rat	> 2000 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg



 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 9 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

<b>Naphtha (petroleum), full-range straight-run (64741-42-0)</b>	
LC50/inhalation/4h/rat	> 5,04 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: No data available
Serious eye damage/eye irritation	: Not classified (Based on available data, the classification criteria are not met.) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met.)
Germ cell mutagenicity	: May cause genetic defects. Benzene
Carcinogenicity	: May cause cancer. Benzene
Reproductive toxicity	: Suspected of damaging fertility. Suspected of damaging the unborn child. n-Hexane Toluene
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met.)
Aspiration hazard	: May be fatal if swallowed and enters airways.

#### Other information

Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxicity : Toxic to aquatic life with long lasting effects.

<b>Naphtha (petroleum), full-range straight-run (64741-42-0)</b>	
LC50 fish 1	82 mg/l
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysisidopsis bahia)
EC50 72h Algae [mg/l] (1)	4700 mg/l (Species: Pseudokirchneriella subcapitata)

### 12.2. Persistence and degradability

Persistence and degradability : Not applicable  
Substance is complex UVCB.

### 12.3. Bioaccumulative potential

Bioaccumulation : Not applicable  
Substance is complex UVCB.


Partition coefficient n-octanol/water : No data available

### 12.4. Mobility in soil

Mobility : No data available  
Substance is complex UVCB

### 12.5. Results of PBT and vPvB assessment

PBT/vPvB data : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).  
This substance is not considered to be very persistent nor very

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 10 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

bioaccumulating (vPvB).

**12.6. Other adverse effects**

Other information : No data available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Product waste: : Handle with care.  
Safe handling: see section 7  
Handling and storage  
Refer to manufacturer/supplier for information on recovery/recycling.  
Collect and dispose of waste product at an authorised disposal facility.  
Do not allow contact with soil, surface or ground water.  
Dispose of empty containers and wastes safely.  
Recycling is preferred to disposal or incineration  
If recycling is not possible, eliminate in accordance with local valid waste disposal regulations

Contaminated packaging : Do not burn, or use a cutting torch on, the empty drum.  
Do not puncture or incinerate.  
Delivery to an approved waste disposal company.  
Handle contaminated packages in the same way as the substance itself.  
Dispose according to legislation.

List of proposed waste codes/waste designations in accordance with EWC : This material and its container must be disposed of as hazardous waste.  
Waste codes should be assigned by the user based on the application for which the product was used.  
The following Waste Codes are only suggestions:  
13 07 02\*  
150110\* - packaging containing residues of or contaminated by dangerous substances

**SECTION 14: Transport information**

**14.1. UN number**

UN number : 1268

**14.2. UN proper shipping name**

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S.  
Proper Shipping Name (IATA) : Petroleum distillates, n.o.s.  
Proper Shipping Name (IMDG) : PETROLEUM DISTILLATES, N.O.S.  
Proper Shipping Name (ADN) : PETROLEUM DISTILLATES, N.O.S.

**14.3. Transport hazard class(es)**


**14.3.1. Overland transport**

Class(es) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code : F1  
ADR/RID-Labels : 3 - Flammable liquid



**14.3.2. Inland waterway transport (ADN)**

ADN : Hazards :3+N2

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 11 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

Class (UN) : 3

**14.3.3. Transport by sea**

Class or Division : 3 - flammable liquids

**14.3.4. Air transport**

Class or Division : 3 - flammable liquids

**14.4. Packing group**

Packing group : I

**14.5. Environmental hazards**

Environmental hazards : p



Other information : ADN : N2.

**14.6. Special precautions for user**

Special precautions for user : No data available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Code: IBC : No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. EU-Regulations**


The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006 :

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008 : Naphtha (petroleum), full-range straight-run

5. Benzene : Benzene

28. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as Carcinogen category 1A or 1B (Table 3.1) or Carcinogen category 1 or 2 (Table 3.2) and listed as follows: Carcinogen category 1A (Table 3.1)/Carcinogen category 1 (Table 3.2) listed in Appendix 1 Carcinogen category 1B (Table 3.1)/Carcinogen category 2 (Table 3.2) listed in Appendix 2 : Naphtha (petroleum), full-range straight-run

29. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as Germ cell Mutagen category 1A or 1B (Table 3.1) or Mutagen category 1 or 2 (Table 3.2) and listed as follows: Mutagen category 1A (Table 3.1)/Mutagen category 1 (Table 3.2) listed in Appendix 3 Mutagen category 1B (Table 3.1)/Mutagen category 2 (Table 3.2) listed in Appendix 4 : Naphtha (petroleum), full-range straight-run

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 12 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

: Naphtha (petroleum), full-range straight-run

48. Toluene

: Toluene

This product contains an ingredient according to the candidate list of Annex XIV of the REACH Regulation 1907/2006/EC.

: none

Authorisations

: Not applicable

Take note of Directive 92/85/EEC on the safety and health at work of pregnant workers.

Take note of Directive 94/33/EC on the protection of young people at work.

#### 15.1.2. National regulations

DE : WGK

: 3

DE : German storage class (LGK)

: LGK 3 - Flammable liquid materials (Flashpoint < 55 °C)

DE : TA-Luft

: Organic Substances, Carcinogenic substances, Mutagenic

DE : Technische Regeln für Gefahrstoffe (TRGS)

: applicable

DE : Risk classification according to VbF

: A I - Liquids with a flashpoint below 21°C

FR : Installations classées

: 143X; ;113X; 117X

NL : ABM

: 2 - May cause heritable genetic damage. (A)

NL : NeR (Nederlandse emissie Richtlijn)

: Organic substances in vapour or gaseous form

#### 15.2. Chemical safety assessment


Chemical Safety Assessment

: For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

Full text of R-, H- and EUH-phrases:


Aquatic Chronic 2	: Hazardous to the aquatic environment - chronic hazard category 2
Asp. Tox. 1	: Aspiration hazard, Category 1
Carc. 1A	: Carcinogenicity, Category 1A
Carc. 1B	: Carcinogenicity, Category 1B
Eye Irrit. 2	: Serious eye damage/eye irritation Category 2
Flam. Liq. 1	: Flammable liquids, Category 1
Flam. Liq. 2	: Flammable liquids, Category 2
Muta. 1B	: Germ cell mutagenicity, hazard categories 1B
Repr. 2	: Reproductive toxicity, Hazard Category 2
Repr. 2	: Reproductive toxicity, Hazard Category 2
Repr. 2	: Reproductive toxicity, Hazard Category 2
Skin Irrit. 2	: Skin corrosion/irritation, Category 2
STOT RE 1	: Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	: Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	: Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	: Extremely flammable liquid and vapour.
H225	: Highly flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H340	: May cause genetic defects.
H350	: May cause cancer.

 <b>MERCURIA</b> <small>MERCURIA ENERGY TRADING BV</small>	<b>SAFETY DATA SHEET</b>	Page : 13 / 14
	<b>Naphtha (petroleum), full-range straight-run</b>	Revision nr : 1
		Issue date : 04/02/2015
		Supersedes :

H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
R11	: Highly flammable.
R12	: Extremely flammable.
R36/38	: Irritating to eyes and skin.
R38	: Irritating to skin.
R45	: May cause cancer.
R46	: May cause heritable genetic damage.
R48/20	: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R48/23/24/25	: Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R51/53	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	: Possible risk of impaired fertility.
R63	: Possible risk of harm to the unborn child.
R65	: Harmful: may cause lung damage if swallowed.
R67	: Vapours may cause drowsiness and dizziness.
F	: Highly flammable
F+	: Extremely flammable
N	: Dangerous for the environment
T	: Toxic
Xi	: Irritant
Xn	: Harmful

Key literature references and sources for data : European Chemicals Agency  
CSR

Abbreviations and acronyms : ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin  
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC  
IATA = International Air Transport Association  
IMDG = International Maritime Dangerous Goods Code  
LEL = Lower Explosive Limit/Lower Explosion Limit  
UEL = Upper Explosion Limit/Upper Explosive Limit  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals  
N = Dangerous for the environment  
TWA = time weighted average  
PBT = persistent, bioaccumulating and toxic (PBT).  
vPvB = very persistent and very bioaccumulating  
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)  
T = Toxic  
TLV = Threshold limits  
STEL = Short term exposure limit  
DNEL = Derived No Effect Level  
CSR = Chemical Safety Report  
EC50 = Median Effective Concentration  
UVCB = Substance of unknown or variable composition, complex reaction products or biological material (UVCB)  
DMEL = Derived minimal effect level  
PNEC = Predicted No Effect Concentration  
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)  
LC50 = Median lethal concentration  
LD50 = Median lethal dose

	<b>SAFETY DATA SHEET</b>	Page : 14 / 14
		Revision nr : 1
	<b>Naphtha (petroleum), full-range straight-run</b>	Issue date : 04/02/2015
		Supersedes :

LL50 = Median lethal level  
 EL50 = Median effective level  
 ErC50 = EC50 in terms of reduction of growth rate  
 ErL50 = EL50 in terms of reduction of growth rate  
 NOEL = No-observed-effect level  
 NOEC = No observed effect concentration  
 NOELR = No observed effect loading rate  
 NOAEC = No observed adverse effect concentration  
 NOAEL = No observed adverse effect level  
 EWC = European Waste Catalogue  
 NA = Not applicable  
 N.O.S. = Not Otherwise Specified  
 VOC = Volatile organic compounds  
 Quantitative structure-activity relationship (QSAR)  
 ABM = Algemene beoordelingsmethodiek  
 STOT = Specific Target Organ Toxicity  
 BTT = Breakthrough time (maximum wearing time)

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.