	SAFETY DATA SHEET	Page : 1 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name : Gasoline
EC Index : 649-378-00-4
EC-No. : 289-220-8
CAS-No. : 86290-81-5
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Mercuria Energy Trading B.V. supplying for and behalf of Mercuria Energy Trading S.A.
Euclideslaan 131
3584 BR Utrecht - Netherlands
T +31 30 608 61 30 - F +31 30 254 11 26
Technical support: +1 720 214 6215
REACH@Mercuria.com

1.4. Emergency telephone number

Emergency number : +32 3 575 11 30 (SGS 24/7 Emergency Hotline)


Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 1 H224
Skin Irrit. 2 H315
Muta. 1B H340
Carc. 1B H350
Repr. 2 H361fd
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Chronic 2 H411

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 2 / 19
	Gasoline	Revision nr : 2.0
		Issue date : 01/07/2021
		Supersedes : 04/02/2015

Full text of H-statements: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word :

Danger

Hazard statements (CLP) :

H224 - Extremely flammable liquid and vapour.
 H304 - May be fatal if swallowed and enters airways.
 H315 - Causes skin irritation.
 H336 - May cause drowsiness or dizziness.
 H340 - May cause genetic defects.
 H350 - May cause cancer.
 H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P201 - Obtain special instructions before use.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 - Avoid release to the environment.
 P280 - Wear eye protection, face protection, protective clothing, protective gloves.
 P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER.
 P331 - Do NOT induce vomiting.

Listed in Annex VI :

EC Index-No. : 649-378-00-4

2.3. Other hazards

Other hazards :

Vapours can form explosive mixtures with air.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII


This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance name : Gasoline
 CAS-No. : 86290-81-5
 EC-No. : 289-220-8
 EC Index : 649-378-00-4

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 3 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Gasoline	(CAS-No.) 86290-81-5 (EC-No.) 289-220-8 (EC Index) 649-378-00-4	100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361fd STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index) 601-021-00-3	≥ 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
n-Hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index) 601-037-00-0	≥ 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
benzene	(CAS-No.) 71-43-2 (EC-No.) 200-753-7 (EC Index) 601-020-00-8	≥ 0,1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304

Specific concentration limits:

Substance name	Product identifier	Specific concentration limits
n-Hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index) 601-037-00-0	(5 ≤C < 100) STOT RE 2, H373

Full text of H- and EUH-statements: see section 16


3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Treat symptomatically. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. Give oxygen or artificial respiration if necessary. Get medical advice/attention.
Skin contact	: Wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician. Remove contaminated clothing and wash it before reuse.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Do NOT induce vomiting. Get immediate medical advice/attention.

	SAFETY DATA SHEET	Page : 4 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause drowsiness or dizziness. Vapours may cause drowsiness and dizziness. The following symptoms may occur: Cough. Mental confusion. Headache.
Skin contact	: Causes skin irritation. The following symptoms may occur: erythema (redness).
Eyes contact	: Contact with eyes may cause irritation. The following symptoms may occur: erythema (redness).
Ingestion	: May be fatal if swallowed and enters airways. The following symptoms may occur: Central nervous system depression.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause cancer. May cause genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Alcohol resistant foam. dry extinguishing powder. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Heating will cause a rise in pressure with a risk of bursting. Vapours may form explosive mixture with air. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Hazardous decomposition products. Carbon oxides (COx). Organic compounds. as appropriate : Hydrogen sulfide (H ₂ S). Sulphur oxides. Sulphuric acid. Do not allow run-off from fire-fighting to enter drains or water courses.
------------------	---

5.3. Advice for firefighters


Firefighting instructions	: Special protective equipment for firefighters. In case of fire: Wear self-contained breathing apparatus. Use water spray or fog for cooling exposed containers. Evacuate personnel to a safe area. Do not allow run-off from fire-fighting to enter drains or water courses.
---------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel	: Evacuate personnel to a safe area. Stay upwind/keep distance from source. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Avoid contact with skin, eyes and clothing. Do not breathe vapour/aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools. As appropriate : Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.
-----------------------------	--

	SAFETY DATA SHEET	Page : 5 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8 .

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Cover the spilled liquid product with foam to slow down evaporation. Stop leak if safe to do so. Clean-up methods - small spillage: Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite or powdered limestone, Collect in closed and suitable containers for disposal. Clean-up methods - large spillage: Cover the spilled liquid product with foam to slow down evaporation, Dam up, Recover large spills by pumping (use an explosion proof or hand pump), Keep in suitable, closed containers for disposal. Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Dispose of waste product or used containers according to local regulations.

6.4. Reference to other sections


Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Avoid contact with skin, eyes and clothing. Do not breathe vapour/aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools. Take any precaution to avoid mixing with combustibles... See also section 10. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. as appropriate. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Hygiene measures : Keep good industrial hygiene. Wash hands immediately after handling the product. Remove contaminated clothing and shoes. When using do not eat, drink or smoke. Separate working clothes from town clothes. Keep away from food, drink and animal feedingstuffs. Wash contaminated clothing before reuse.

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 6 / 19
	Gasoline	Revision nr : 2.0
		Issue date : 01/07/2021
		Supersedes : 04/02/2015

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Storage of flammable liquids. Store in a dry, cool and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Open valve slowly to avoid pressure shock. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. Protect from sunlight. Bund storage facilities to prevent soil and water pollution in the event of spillage. As appropriate : Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Packaging materials : Keep only in the original container. Suitable material: Mild steel, Stainless steel. Unsuitable material: Synthetic material.


7.3. Specific end use(s)

see attached exposure scenario.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

benzene (71-43-2)		
Bulgaria	OEL TWA [ppm]	1 ppm
Hungary	AK (OEL TWA)	3,25 mg/m ³
Gasoline (86290-81-5)		
Belgium	OEL TWA	903 mg/m ³
Belgium	OEL TWA [ppm]	300 ppm
Belgium	OEL STEL	1501 mg/m ³
Belgium	OEL STEL [ppm]	500 ppm
Croatia	GVI (OEL TWA) [2]	300 ppm (low-boiling, unspecified)
Croatia	KGVI (OEL STEL) [ppm]	500 ppm
Czech Republic	PEL (OEL TWA)	400 mg/m ³ (Gasoline, technical mixture)
Estonia	OEL TWA	200 mg/m ³ (aromatic compounds calculated as Trimethylbenzene 50% (Petroleum))
Estonia	OEL STEL	300 mg/m ³
Ireland	OEL TWA [2]	300 ppm
Ireland	OEL STEL [ppm]	500 ppm
Lithuania	IPRV (OEL TWA)	200 mg/m ³ (table 2, limit values for hydrocarbons)
Lithuania	TPRV (OEL STEL)	300 mg/m ³ (table 2, limit values for hydrocarbons)
Netherlands	MAC-TGG (OEL TWA)	240 mg/m ³
Netherlands	MAC-15 (OEL STEL)	480 mg/m ³
Portugal	OEL TWA [ppm]	300 ppm
Portugal	OEL STEL [ppm]	500 ppm
Spain	VLA-ED (OEL TWA) [2]	300 ppm (manufacturing, commercialization and use restrictions according to REACH)
Sweden	NGV (OEL TWA)	250 mg/m ³ (approximate value that can be used in preventive protection (Petroleum fuels))

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 7 / 19
	Gasoline	Revision nr : 2.0
		Issue date : 01/07/2021
		Supersedes : 04/02/2015

Gasoline (86290-81-5)		
Switzerland	MAK (OEL TWA) [1]	1100 mg/m ³
Switzerland	MAK (OEL TWA) [2]	300 ppm
Australia	OES TWA [1]	900 mg/m ³
USA - ACGIH	ACGIH OEL TWA [ppm]	300 ppm
USA - ACGIH	ACGIH OEL STEL [ppm]	500 ppm


8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. See Section 7 for information on safe handling. Use only outdoors or in a well-ventilated area. Store locked up. Handle substance within a closed system. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Wear chemically resistant gloves (tested to EN374) . NBR (Nitrile rubber) > 0,3 mm, BTT: >480 min. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN 166). goggles
Body protection	: Wear suitable coveralls to prevent exposure to the skin. Use chemically protective clothing. Antistatic clothing. In case of large spillages: Wear full chemical protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Filter type: ABEK (EN 141). Half-face mask (DIN EN 140). full face mask (DIN EN 136). Self-contained open-circuit compressed air breathing apparatus (EN 137). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: liquid.
Colour	: Colourless.
Odour	: petroleum hydrocarbon odour.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: < -60 °C
Freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: < -40 °C (closed cup)
Auto-ignition temperature	: 280 – 470 °C (at 1013 hPa)
Decomposition temperature	: No data available

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	<h1>SAFETY DATA SHEET</h1>	Page : 8 / 19
		Revision nr : 2.0
	<h2>Gasoline</h2>	Issue date : 01/07/2021
		Supersedes : 04/02/2015

Flammability (solid, gas)	: Not applicable,liquid
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Solubility	: No additional information available. Water: 30 – 100 mg/l (at 20 °C)
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: No data available
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapour. Reference to other sections 10.4 & 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions


Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

oxidising substances. See Section 7 for information on safe handling.

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 9 / 19
	Gasoline	Revision nr : 2.0
		Issue date : 01/07/2021
		Supersedes : 04/02/2015

10.6. Hazardous decomposition products

Burning produces noxious and toxic fumes. Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

benzene (71-43-2)	
LD50/oral/rat	> 2000 mg/kg
LD50/dermal/rabbit	> 8200 mg/kg
LC50/inhalation/4h/rat	44,66 mg/l/4h

Toluene (108-88-3)	
LD50/oral/rat	2600 mg/kg
LD50/dermal/rabbit	12000 mg/kg
LC50/inhalation/4h/rat	12,5 mg/l/4h


n-Hexane (110-54-3)	
LD50/oral/rat	25 g/kg
LD50/dermal/rabbit	3000 mg/kg
LC50/inhalation/4h/rat (ppm)	48000 ppm/4h

Gasoline (86290-81-5)	
LD50/oral/rat	92 g/kg
LD50/dermal/rat	> 2000 mg/kg
LD50/dermal/rabbit	> 5 ml/kg
LC50/inhalation/4h/rat	> 5,2 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: No data available
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: May cause genetic defects. Benzene
Carcinogenicity	: May cause cancer. Benzene
Reproductive toxicity	: Suspected of damaging fertility. Suspected of damaging the unborn child. n-Hexane Toluene
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: May be fatal if swallowed and enters airways.

Gasoline (86290-81-5)	
Kinematic viscosity	No data available
Human evidence for classification	Yes

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	<h1>SAFETY DATA SHEET</h1>	Page : 10 / 19
		Revision nr : 2.0
	<h2>Gasoline</h2>	Issue date : 01/07/2021
		Supersedes : 04/02/2015

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

11.2.2 Other information

Other information : Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

benzene (71-43-2)

LC50 - Fish [1]	10,7 – 14,7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	5,3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	8,76 – 15,6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	10 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	29 mg/l (Species: Pseudokirchneriella subcapitata)

Toluene (108-88-3)


LC50 - Fish [1]	15,22 – 19,05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	12,6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	5,46 – 9,83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11,5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12,5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)

n-Hexane (110-54-3)

LC50 - Fish [1]	2,1 – 2,98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
-----------------	---

Gasoline (86290-81-5)

LC50 - Fish [1]	82 mg/l
EC50 - Crustacea [1]	7,6 mg/l

	SAFETY DATA SHEET	Page : 11 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

EC50 72h - Algae [1]	56 mg/l (Species: Pseudokirchneriella subcapitata)
----------------------	--

12.2. Persistence and degradability

Gasoline (86290-81-5)	
Persistence and degradability	Not applicable.

12.3. Bioaccumulative potential

Gasoline (86290-81-5)	
Partition coefficient n-octanol/water	No data available

benzene (71-43-2)	
BCF - Fish [1]	3,5 – 4,4
Partition coefficient n-octanol/water	2,1

Toluene (108-88-3)	
Partition coefficient n-octanol/water	2,7

12.4. Mobility in soil

Gasoline (86290-81-5)	
Ecology - soil	No data available. Substance is complex UVCB.

12.5. Results of PBT and vPvB assessment


Gasoline (86290-81-5)	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

12.7. Other adverse effects

Additional information : No data available

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 12 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015






SECTION 13: Disposal considerations


13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Handle with care. See Section 7 for information on safe handling. Handling and storage. Refer to manufacturer/supplier for information on recovery/recycling. Collect and dispose of waste product at an authorised disposal facility. Do not allow to enter into surface water or drains. Dispose of empty containers and wastes safely. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.
Additional information	: Do not burn, or use a cutting torch on, the empty drum. Do not puncture or incinerate. Delivery to an approved waste disposal company. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.
European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)	: This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 07 02* 150110* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1268	1268	1268	1268	1268
14.2. UN proper shipping name				
PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.
Transport document description				
UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1268 Petroleum distillates, n.o.s., 3, I, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, I, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
I	I	I	I	I
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
ADN : N2.				

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	<h1>SAFETY DATA SHEET</h1>	Page : 13 / 19
		Revision nr : 2.0
	<h2>Gasoline</h2>	Issue date : 01/07/2021
		Supersedes : 04/02/2015

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : F1
Special provisions : 363
Limited quantities (ADR) : 500ml
Excepted quantities (ADR) : E3
Packing instructions (ADR) : P001
Mixed packing provisions (ADR) : MP7, MP17
Portable tank and bulk container instructions (ADR) : T11
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : L4BN
Vehicle for tank carriage : FL
Transport category (ADR) : 1
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :

33
1268


Tunnel restriction code : D/E
EAC code : 3YE

- Transport by sea

Special provisions (IMDG) : 363
Limited quantities (IMDG) : 500 ml
Excepted quantities (IMDG) : E3
Packing instructions (IMDG) : P001
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : E
Properties and observations (IMDG) : Immiscible with water.

- Air transport

PCA Excepted quantities (IATA) : E3
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : 351
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 361

	SAFETY DATA SHEET	Page : 14 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A3
ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 363
Limited quantities (ADN) : 500 ml
Excepted quantities (ADN) : E3
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
Special provisions (RID) : 363
Limited quantities (RID) : 500ml
Excepted quantities (RID) : E3
Packing instructions (RID) : P001
Mixed packing provisions (RID) : MP7, MP17
Portable tank and bulk container instructions (RID) : T11
Portable tank and bulk container special provisions (RID) : TP1, TP8
Tank codes for RID tanks (RID) : L4BN
Transport category (RID) : 1
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.


SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

5. Benzene	benzene
28. Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.	Gasoline ; benzene ; Gasoline
29. Substances which are classified as germ cell mutagen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 3 or Appendix 4, respectively.	Gasoline ; benzene ; Gasoline
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Gasoline ; Toluene ; n-Hexane ; benzene

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 15 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Gasoline ; Toluene ; n-Hexane ; benzene
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Gasoline ; n-Hexane
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Gasoline ; Toluene ; n-Hexane ; benzene ; Gasoline
48. Toluene	Toluene
72. The substances listed in column 1 of the Table in Appendix 12	benzene


Gasoline is not on the REACH Candidate List

Gasoline is not on the REACH Annex XIV List

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4330.text	Liquides inflammables de catégorie 1, liquides inflammables maintenus à une température supérieure à leur point d'ébullition, autres liquides de point éclair inférieur ou égal à 60° C maintenus à une température supérieure à leur température d'ébullition ou dans des conditions particulières de traitement, telles qu'une pression ou une température élevée (1).		
4330.1	La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant : 1. Supérieure ou égale à 10 t (1) Conformément à la section 2.6.4.5 de l'annexe I du règlement (CE) n° 1272/2008, il n'est pas nécessaire de classer les liquides ayant un point d'éclair supérieur à 35° C dans la catégorie 3 si l'épreuve de combustion entretenue du point L 2, partie III, section 32, du Manuel d'épreuves et de critères des Nations unies a donné des résultats négatifs. Toutefois, cette remarque n'est pas valable en cas de température ou de pression élevée, et ces liquides doivent alors être classés dans cette catégorie. Quantité seuil bas au sens de l'article R. 511-10 : 10 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 t.	A	2
4330.2	La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant : 2. Supérieure ou égale à 1 t mais inférieure à 10 t (1) Conformément à la section 2.6.4.5 de l'annexe I du règlement (CE) n° 1272/2008, il n'est pas nécessaire de classer les liquides ayant un point d'éclair supérieur à 35° C dans la catégorie 3 si l'épreuve de combustion entretenue du point L 2, partie III, section 32, du Manuel d'épreuves et de critères des Nations unies a donné des résultats négatifs. Toutefois, cette remarque n'est pas valable en cas de température ou de pression élevée, et ces liquides doivent alors être classés dans cette catégorie. Quantité seuil bas au sens de l'article R. 511-10 : 10 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 t.	DC	
4511.text	Dangereux pour l'environnement aquatique de catégorie chronique 2.		

	SAFETY DATA SHEET	Page : 16 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

4511.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	A	1
4511.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 100 t mais inférieure à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	DC	

Germany

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV)
Risk classification according to VbF : A I - Liquids with a flashpoint below 21°C
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

TA Luft : Organic Substances

Netherlands

Waterbezwaarlijkheid : A (2) - Vergiftig voor in water levende organismen
kan in het aquatische milieu op lange termijn schadelijke effecten veroorzaken
Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen : Gasoline is listed
SZW-lijst van mutagene stoffen : Gasoline is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Classification remarks : Add boilingpoint; Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product


15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out

SECTION 16: Other information

Indication of changes:


	SDS Version (obsolete)	Modified	
	Issue date	Modified	
2.2	Precautionary	Modified	

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	<h1>SAFETY DATA SHEET</h1>	Page : 17 / 19
		Revision nr : 2.0
	<h2>Gasoline</h2>	Issue date : 01/07/2021
		Supersedes : 04/02/2015

	statements (CLP)		
2.3	ED text	Modified	
9.2	Information with regard to physical hazard classes	Added	
9.2	Other safety characteristics	Added	
11.2	Adverse health effects caused by endocrine disrupting properties	Modified	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Modified	
12.7	Other adverse effects	Added	
14.7	Maritime transport in bulk according to IMO instruments	Added	
15.1	Installations classées	Modified	

Abbreviations and acronyms:

ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
N = Dangerous for the environment
TWA = time weighted average
PBT = persistent, bioaccumulating and toxic (PBT).
vPvB = very persistent and very bioaccumulating
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)
T = Toxic
TLV = Threshold limits
STEL = Short term exposure limit
DNEL = Derived No Effect Level
CSR = Chemical Safety Report
EC50 = Median Effective Concentration
UVCB = Substance of unknown or variable composition, complex reaction products or biological material (UVCB)
DMEL = Derived Minimal Effect level
PNEC = Predicted No Effect Concentration
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate
NOEL = no-observed-effect level
NOEC = No observed effect concentration
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
EWC = European waste catalogue

 MERCURIA <small>MERCURIA ENERGY TRADING BV</small>	SAFETY DATA SHEET	Page : 18 / 19
	Gasoline	Revision nr : 2.0
		Issue date : 01/07/2021
		Supersedes : 04/02/2015

	NA = Not applicable
	N.O.S. = Not Otherwise Specified
	VOC = Volatile organic compounds
	Quantitative structure-activity relationship (QSAR)
	ABM = Algemene beoordelingsmethodiek
	STOT = Specific Target Organ Toxicity
	BTT = Breakthrough time (maximum wearing time)


Sources of key data used to compile the datasheet : European Chemicals Agency CSR.

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Assessment/classification CLP. Article 9. Calculation method. Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

	SAFETY DATA SHEET	Page : 19 / 19
		Revision nr : 2.0
	Gasoline	Issue date : 01/07/2021
		Supersedes : 04/02/2015

H411	Toxic to aquatic life with long lasting effects.
------	--

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.